


AVAILABLE  
DOOR SIZES

Standard:

8W X 8H  
8W X 10H  
8W X 12H  
8W X 14H  
10W X 10H  
10W X 12H  
10W X 14H  
10W X 16H  
12W X 10H  
12W X 12H  
12W X 14H  
12W X 16H  
14W X 10H  
14W X 12H  
14W X 14H  
14W X 16H  
16W X 10H  
16W X 12H  
16W X 14H  
16W X 16H


Special order:

6W X 8H  
6W X 10H  
6W X 12H  
18W X 10H  
18W X 12H  
18W X 14H  
18W X 16H




**#2 Square Keyhold Track**

Versatile and popular. For single track runs, space brackets 24" on center. Track is 16 gauge galvanized steel.



**#510 Square Keyhold Track**

Top mount track attaches with 1 1/2" ring shank washer nails. Combination mounting/flushing brackets are projection welded at factory.



**#8 Square Keyhold Track**

No brackets or flashing required with pre-painted white cover; attach with 1 1/2" ring-shank neoprene washer nails.



**RB-309-T Trolley**

This ball bearing trolley combines bolt-through simplicity and economy with pivot-swing action.



**100-HD Trolley**

This economical, yet built for durability, one-piece apron door strap hanger is laterally and vertically adjustable.



**302-T Trolley**

Popular bolt-through design speeds installation. Long 1/2" x 10" offset bolt can be used with a variety of door materials.



**10-FB Flashing Bracket**

Flashing Brackets may be nailed over track to provide support for compatible flashing.



**8-2SFB Track Bracket**

Adjustable face-mount bracket has two mounting holes for 3/8" lag screws or bolts. Flashing bracket is pre-attached at the factory.



**9-2C Track Bracket**

Self clamping single track bracket is also used for joining two pieces of box track.



**9-2S Track Bracket**

Adjustable face-mount bracket has two mounting holes for 3/8" lag screws or bolts.




**2-EB End Blind**

Snaps into bracket to keep track free from birds, weather and other obstructions.



**800 Stay Roller**

Fabricated from 3/16" zinc plated steel, and adjusts from 1" to 3-3/4". Non-marking plastic wheel mounted on sturdy 1/2" bolt.




**#1001 Quick Frame**

Lumber fit for standard 2 x 4 or 2 x 6 and provides smooth, safe sides for door openings.



**#1002 H-Frame**

Designed for use with bi-parting doors, provides concealed mating between units covering both door edges.



**#1003 Bottom Rail**

Attaches to bottom of door and accepts the #64 rail guide to firmly anchor and guide door along building during operation; for doors 1-1/2" thick.

The #1005 Lumber Fit Bottom Rail and Lateral and Vertical Easy Lock Door Systems are also available.

[www.acrmetal.com](http://www.acrmetal.com)




**#64 Rail Guide**

Fabricated from 16 gauge galvanized steel and mounts with #60 brackets. Engages the bottom door guides to hold the door in place.




**#60 Guide Rail Bracket**

Slotted hole in each leg allows both lateral and vertical adjustments.



**520 Door Guide/Stop**

Installs on 6 x 6 post or in concrete, in the center of split doors or a large single door. For use in pairs.



**#68 Door Stop**

For use with #64 bottom door guide. Stops door and prevents from disengaging with guide rail.




**540 Door Stop**

For 2" doors, made from rugged zinc-plated steel and ribbed to increase strength. Holes accept 5/16" bolts or lag screws.




**545 Door Guide/Stop**

This adjustable guide may be expanded in width for doors from 2-1/2" to 6" thick. Curved surface gives natural lead-in and can be mounted sideways for use as a stop.



**560 Jamb Mount Door Stop**

2-1/2" x 8-1/2" galvanized steel unit extends from jamb to stop and holds doors in the open or closed position.



**600 Jamb Latch**

7" jamb latch is used on inside of jamb to secure sliding doors; can be ordered for either right or left hand applications.



**610 Center Door Latch**

Easily and tightly secures bi-parting doors with cam-action latch. A strong bolt hooks at one end to fit strike plate; opposite end is threaded to allow adjustment of latch tension. For wood doors 1-1/2" or thicker.



**630 Sliding Bolt Latch**

Ideal for livestock/horse barns, this heavy duty 1/2" x 10" steel bolt doubles as a handle/pull, and may be used at left or right.



**50-3 Door Pull**

This door pull is 1-1/4" wide and has a 6-5/8" overall length. Retains 1-3/4" deep clearance to allow use with gloved hand.



**50-3W Door Pull**


This door pull is 1-1/4" wide and has a 6-5/8" overall length. Retains 1-3/4" deep clearance to allow use with gloved hand.



**900 Chain Snugger**

Ring and hook simply secure a chain to desired length for holding bi-parting sliding door leaves together.

**Round Track Products** - not stocked at Marshfield, WI or St. Joseph, MN. Call for lead times.



**#3 Slotted Round Keyhold Track**

For smooth, easy gliding operation. 14 gauge galvanized construction in self-cleaning design.



**RBP 203-L Wheel with Ball Bearings**

Adjustable, pivot and swing action with single strap apron.



**203-L Wheel with Bronze Bushings**

Adjustable, pivot and swing action with single strap apron.



**RBP 303-T Wheel with Ball Bearings**

Bolt-through simplicity with swing action.



**303-T Wheel with Bronze Bushings**

Bolt-through simplicity with swing action.



**8-3C Bracket**

Double track bracket (face mount), bolts included.



**8-3CFB Bracket**

Double track bracket. Same as 8-3C but with flashing bracket pre-attached at factory to accept a Double Track Cover.



**3-BC Bracket**

Slide-on bracket face mounts.



**3-FB Flashing Bracket**

Round-up flashing bracket taps in with hammer.



**3-1PC Bracket**

Rivets fit through track keyway slots, allowing track, bracket and cover to be joined.



**SC-3 Track Splice Collar**

Track splice collar.